

Revised 9-16-94

Oil Recommendations for Hi-Performance Outboards

MODELS:

MHP 2.4 L and 2.5 L

Recommended Oil: Mercury Hi-Performance Synthetic Blend 2-Cycle Oil.

Emergency Use Only: If the Hi-Performance 2-Cycle Oil is not available, Quicksilver TC-W 2 or Quicksilver NMMA Certified TC-W3 2-Cycle Oil may be substituted. These oils should not be used on a regular basis.

Mixture: Either of the above oils should be mixed at a ratio of 32:1 or 4 oz. of oil to each gallon of fuel.

MODELS:

MHP Pro-Max and Super Magnum

Recommended Oil: Quicksilver NMMA Certified TC-W3 2-Cycle Oil.

Mixture: Double oil mixture should be used during break-in (refer to Operations and Maintenance Manual). After break-in, oil injection system will supply all the lubricant required.

NOTE: If Quicksilver 2-Cycle Outboard Oil is not available, substitute a 2-Cycle outboard manufacturer's oil that is NMMA certified TC-W3, or another brand of 2-Cycle outboard oil that is NMMA certified TC-W3. The use of an inferior 2-Cycle outboard oil can reduce engine durability. Damage from use of inferior oil may not be covered under the limited warranty.